

WHEEL LOADER SNOWBLOWER



**Fits CAT® 918, 924, 926, 930,
938 K/M Series Wheel Loaders!**

Standard Features:

- **100% Hydraulically Powered** – Low cost of operation and minimal wear on parts
- **Side Discharge** – Efficiently throws snow to the right or left without using the spout
- **Telescoping Truck Loading Spout** – Reach the highest of trucks seamlessly
- **Rotary Spout** – 270° rotation can be turned with a small finger movement
- **Spout Deflector** – Hydraulically powered for precise control and accurate placement
- **Digital Display** – Mount in the cab to monitor blower performance
- **Small Control Module** – Smoothly manipulate all hydraulic functions with ease
- **Enclosed Auger Chain** – #80 Heavy Duty chain and spring tensioned idler sprocket
- **No Shear Pins** – Abrupt stops will trigger oil to bypass protecting the blower
- **Quick-Tach** – Multiple options to match various wheel loader configurations
- **Skid Shoes** – Steel shoes are adjustable, replaceable and will protect the unit from excessive wear
- **Heavy Duty Double Auger** – Includes 16" flighting and rugged 1 1/2" grease-able bearings
- **Tiger Teeth** – Innovative design chews up hard packed snow and ice
- **Grader Blade** – Made from American steel which bolts on quickly and is replaceable for ultimate machine protection
- **Robust Powder Coated Paint** – Shot blasted bare metal, then coated and baked in excess of 400 degrees for the toughest finish available
- **Continually Innovating** – With marketing demand, HitchDoc® is engineering this blower to fit more CAT® Wheel Loader models.



Contact for questions about new potential machines or series!



I-90 & US 71 | Jackson MN
800.446.8222 | 507.847.4049 | Fax 507.847.5100
Sales@HitchDoc.com | ISO 9001 Certified

WWW.HITCHDOC.COM



WHEEL LOADER SNOWBLOWER



HDS 9200 Specifications:

- Cutting width: 108" (9ft)
- Overall width: 114"
- Cutting height: 45"
- Overall height (w/truck loading spout): 127"
- Weight: 5200 lbs
- Fan Dimensions: 32" diameter
- Number of fan paddles: 5
- Fan material: 3/8"
- Chute discharge height: 105" to 150" (deflector down)
- Hydraulic rotating fan housing for 45° RH or LH side discharge
- Drive requirements (wheel loader): 40-50 gpm at 4000psi



How to Order:

All HitchDoc® Wheel Loader SnowBlowers are designed and built to best fit your specific machine. To ensure proper ordering, please follow the steps below.

Step 1: Base Model

Order HDS 9200 – 9 ft. width, dual auger, hydraulic drive, rotating fan housing, truck loading chute, system hydraulics & wiring for CAT® 918, 924, 926, 930, 938 models

Step 2: Quick-Tach Adapter, Must Select 1

HDS 9201 – CAT® Fusion Mount for CAT® 924, 926, 930 & 938 models
HDS 9205 – CAT® Integrated Tool Carrier for CAT 918 models

Step 3: Loader Hydraulic Kit, Must Select 1

HDS 9202 – 1" Coupler, Case Drain & Return Bypass Kit
HDS 9209 – Coupler, Case Drain & Return Bypass Kit for CAT® 918

Step 4: Cab Control Kit

Order HDS 9203 – CAN-bus system wiring for loader, in-cab controls and display

Step 5: Motor Kit, Must Select 1

HDS 9204 – 40 GPM & 12 VDC for CAT® 918 models
HDS 9207 – 40 GPM & 24 VDC for CAT® 924, 926, 930 & 938 models
HDS 9208 – 50 GPM & 24 VDC for CAT® 930 & 938 models

CAT® is a registered trademark of Caterpillar, Inc., which does not manufacture nor endorse this product. HitchDoc® and the eagle design are registered trademarks of C and B Manufacturing, Inc., d/b/a HitchDoc, an independent manufacturer of machinery compatible with the aforesaid payloaders.

For more information, contact your local dealer or Sales@HitchDoc.com

WWW.HITCHDOC.COM

