

BOX STYLE SEED CART

PATENT PENDING



**UNLOAD SEED BOXES
EFFORTLESSLY!**



General Specifications:

- Electric Start Gas Honda™ Motor
- Absolute clean out slopes of 40°
- Ultimate user experience with a wireless remote to control the all hydraulic functions
- DOT compliant and road-ready trailers
- Durable powder-coat finish



Auger Box Cart Specifications:

- Patented Auger reverser virtually eliminates seed loss
- Remote functions: Auger On/Off, Auger Fold/Unfold
- Poly-cupped auger for minimal seed damage
- 15' 7" hydraulic folding auger
- 19' telescoping downspout with 3 stages



Conveyor Box Cart Specifications:

- 20" long cleated conveyor
- 180° conveyor rotation
- Hydraulic height adjustment
- Remote functions: Conveyor On/Off, Left/Right Conveyor Rotation, Conveyor Up/Down, Slide Gate Open/Close



**TRANSFORM YOUR TRAVIS SEED CART INTO
MORE WITH A SEED OR FUEL POD!**



1-90 & US 71 | Jackson, MN
800.446.8222 | 507.847.4049 | Fax 507.847.5100
Sales@HitchDoc.com | ISO 9001 Certified

WWW.HITCHDOC.COM

BOX STYLE SEED CART

PATENT PENDING



AUGER OR CONVEYOR; Travis Seed Cart is what you need!

Seamlessly control your seed transfer from bulk box to planter with a cart that has a low center of gravity and HitchDoc's reliable, self-contained hydraulic system. Travis Seed Carts are designed to perfectly fit your operation's needs, whether you need a poly-cupped auger system or cleated conveyor system. Both systems handle corn, beans, oats, wheat and other small grains with care and ease for a quick, yet safe, move to the planter.



OVERALL SPECS

2000 SERIES

4000 SERIES

6000 SERIES

Capacity	2 seed box	4 seed box	6 seed box
Overall Width	101"	101"	101"
Motor	8 HP Honda™	8 HP Honda™	13 HP Honda™
Color Options	Red, Black, Green, Gray or Tan	Red, Black, Green, Gray or Tan	Red, Black, Green, Gray or Tan
Scale Options	Non-Scale, Ready or Included	Non-Scale, Ready or Included	Non-Scale, Ready or Included

AUGER STYLE

Auger Specs	7" tube & 6" poly-cupped auger	7" tube & 6" poly-cupped auger	7" tube & 6" poly-cupped auger
Overall Length	164"	BP=209" GN=248"	323"
Unload Rate	625 lbs./min.	625 lbs./min.	625 lbs./min.
Axles	3,500# Rubber Dual Torsion	7,000# Rubber Dual Torsion	10,000# Rubber Dual Torsion
Tow Options	Bumper Pull or Skid Model	Bumper Pull, Gooseneck or Skid Model	Gooseneck
Transport Height	120"	120"	120"

CONVEYOR STYLE

Conveyor Specs	6" tube, 8" cleated belt	6" tube, 8" cleated belt	NA
Overall Length	319"	-	NA
Unload Rate	800 lbs./min	800 lbs./min	NA
Axles	4,500# Rubber Dual Torsion	-	NA
Tow Options	Bumper Pull	Bumper Pull or Gooseneck	NA
Transport Height	134"	-	NA

Options:

- Dry Talc Kit
- Auto Shut Off Scale
- Patented Seed Pod
- Patent Pending Fuel Pod
- Dealer Scale Install
- Liquid Inoculator



For more information, contact your local dealer or Sales@HitchDoc.com