

FUEL TRAILERS



BRING FUEL TO YOUR EQUIPMENT, NOT YOUR EQUIPMENT TO FUEL

Standard Features:

- **Efficiency & Profitability** – Bring fuel to your equipment, not your equipment to fuel. Trailers are equipped with quality pumps and durable construction to be dependable year after year
- **Dual Platforms** – With front and rear work platforms, trailers have ultimate accessibility to the tank as well as room to haul a utility box, air compressor, generator or other ancillary equipment
- **DOT Compliant** – Fuel Trailers are assembled with electric brakes, tail lights, running lights, and safety markings allowing them to be driven off the lot and get straight to work
- **Independent Features** – Fenders and tanks are independent and bolted on the trailer frame creating the ability to change sizes or add features as an operation grows and changes
- **Rubber Torsion Axles** – Our suspension minimizes any road bounce while traveling full or empty, protecting your investment from unnecessary fatigue.
- **Long-lasting Finish** – Baked at 400° and thoroughly inspected, our finish is up to withstand harsh conditions. Custom color options are available.
- **Overbuilt to Outlast** – Double welded, certified US Prime Steel, and inspected against the highest quality standards ensures our fuel cart will keep your machinery fleet running for years.
- **Full-Width Baffles** – Each tank has dual baffles running the complete width of the tank to minimize fuel sloshing and improve the trailer ride across any terrain



I-90 & US 71 | Jackson MN
800.446.8222 | 507.847.4049 | Fax 507.847.5100
Sales@HitchDoc.com | ISO 9001 Certified

WWW.HITCHDOC.COM



FUEL TRAILERS



General Specifications:

- 2" anti-slosh tank filler cap & vent
- Cap vents at 2.5 PSI
- 10 micron filter
- 1 1/2" Drain Plug
- Adjustable 2 5/16" ball hitch
- 7,000 lb. square lift jack with bolt-on plate for easy removal
- Heavy gauge American steel
- Automatic shutoff nozzle

Popular Options:

- **Solar Panel Kit** – Factory installed charging kit comes with bolt-on panel, charge controller, and battery voltage monitor to pump fuel using solar energy
- **Nose Storage Compartment** – An additional bolt-on feature that can be easily added or removed at any point to assist in transporting supplies or tools to the field or jobsite
- **Rock Guard Kit** – Aluminum diamond plate applied to areas heavily hit with road debris.



	Fuel Pump	Hose	Tires	Overall Height	Overall Length	Empty Weight	Loaded Weight
HFC 500	15 GPM	3/4"x20'	205/75/15	4'10"	14'6"	2,540 lbs	6,090 lbs
HFC 750	15 GPM	3/4"x20'	235/80/16	5'6"	14'6"	2,650 lbs	7,975 lbs
HFC 990	15 GPM	3/4"x20'	235/80/16	6'5"	14'6"	2,830 lbs	9,860 lbs
HFC 990XL	25 GPM	1"x35' w/ retractable reel	235/80/16	6'3"	19'7"	5,700 lbs	12,730 lbs

Full Option List Includes:

Heavy duty battery kit, 1 custom color finish, aluminum rims, 25 or 50 GPM fluid meters, 25 GPM electric pump, 40 GPM gas pump with electric start, 35' hose with retractable reel, 60 or 100 gallon DEF tanks, 25' DEF hose, 110V DEF heater, Workmen's Kit (990XL only, includes an air compressor, generator and welder), 990XL toolbox, 3" pintle hitch

HFC990

HFC750

HFC500



For more information, contact your local dealer or Sales@HitchDoc.com

WWW.HITCHDOC.COM

MADE IN
USA