SKID STEER SNOWBLOWER







Standard Features:

- 100% Hydraulically Powered All motors including the fan, auger, spout and deflector cylinder are easily controlled from the comfort of your cab
- Long Term Protection Our design has enclosed the auger motor and included ¼ inch end plates for added protection to your machine and the working parts from the elements
- Bypass Relief System High pressure bypass relief system eliminates the need for shear pins and will help protect the blower from sudden stops
- Adjustable Depth Guides Manually change the pin on the skid shoes to control blade height
- **Unbreakable Auger** Single auger with 6 inch center tube and 16 inch diameter laced with Tiger Teeth chew through heavy, wet snow or ice without any issues
- High Visibility Finish With a yellow, powder-coat finish, this snow blower will maintain a sharp, clean appearance season after season
- Overbuilt to Outlast Made from American steel in the Midwest, this blower is compiled of a 7 gauge fan housing and 10 gauge blower shell
- Replaceable Cutting Edge Bolt-on, hardened steel cutting edge is easy to remove and replace after a long use history
- Quick-Tach Mounting Plate A universal mount plate lets you easily attach this blower to most skid steer makes and models
- **Continual Improvement** At HitchDoc, we take our products out year after year and push them to the breaking point to maintain our high quality and performance levels





I-90 & US 71 | Jackson MN 800.446.8222 | 507.847.4049 | Fax 507.847.5100 Sales@HitchDoc.com | ISO 9001 Certified

SKID STEER SNOWBLOWER





How to Order:

All HitchDoc Skid Steer SnowBlowers are designed and built to best fit your specific machine. To ensure proper ordering, please work with your local HitchDoc Dealer, Sales@HitchDoc.com or 800-446-8222.

Step 1

Select the width that best fits your snow management needs: 68 inch, 72 inch or 84 inch.

Step 2

Select the appropriate motor package based on the gallons per minute of the machine that will run the blower. Select any optional high flow kits to best fit your machine.

Step 3

Select the appropriate electrical harness based on the make and model of your machine. Options are Universal, 8-Pin or 14-Pin.

| Specifications: | HDS 68SS | HDS 72SS | HDS 84SS |
|------------------------|--------------|--------------|--------------|
| Fan | 22", 5 Blade | 22", 5 Blade | 22", 5 Blade |
| Fan Depth | 6.5" | 6.5" | 6.5" |
| Fan Blade | 1/4" | 1⁄4" | 1⁄4" |
| Auger Diameter | 16" | 16" | 16" |
| Spout Opening | 7" | 7" | 7" |
| Spout Rotation | 270° | 270° | 270° |
| Housing Height | 32" | 32" | 32" |
| Overall Height | 67" | 67" | 67" |
| Cutting Width | 69.7" | 73.7" | 85.7" |
| Overall Width | 73.5" | 77.5" | 89.5" |
| Approx. Weight | 915 lbs. | 950 lbs. | 1,050 lbs. |

For more information, contact your local dealer or Sales@HitchDoc.com

