

WHEEL LOADER SNOWBLOWERS



HDS9200



HDS7100



HDS7101



BLOWER PACKAGES AVAILABLE FOR HYDROSTATIC DRIVE LOADERS!

Standard Features:

- **100% Hydraulically Powered:** Low cost of operation, minimal wear on parts, and low maintenance for easy transitions into snowy weather
- **Bypass Relief System:** Eliminates the need for shear pins or gearboxes which can break under load and cause expensive and timely repairs.
- **Rotary Spout:** 270° rotation can be turned with a small finger movement
- **Spout Deflector:** Hydraulically powered for precise control and accurate placement
- **Digital Display and Pendant:** Mount in the cab to monitor blower performance and smoothly manipulate hydraulic functions (Optional on HDS7100)
- **Quick-Tach:** Multiple options to match various wheel loader configurations
- **Skid Shoes:** Steel shoes are adjustable, replaceable and will protect the unit from excessive wear
- **Side Skid Plates:** Replaceable curb skids to protect unit from excessive wear
- **Tiger Teeth:** Innovative design chews up hard packed snow and ice
- **Robust Paint:** Toughest available high-visibility paint to ensure long-term durability and ultimate safety precautions
- **American Made:** We use the highest quality USA components which qualify for the Buy American certification
- **Green Compliant:** Eliminates the need for a second diesel motor, making our blowers more eco-friendly than competitors' models
- **Continually Improving:** Are you wondering if we fit your loader? Contact us today to see



I-90 & US 71 | Jackson, MN
800.446.8222 | 507.847.4049 | Fax 507.847.5100
Sales@HitchDoc.com | ISO 9001 & 14001



www.HitchDoc.com

WHEEL LOADER SNOWBLOWERS



	Cut Width	Cut Height	Overall Width	Overall Height	Weight	Auger	Chute Discharge Height	Hydraulic Requirements
HDS 9200	108"	45"	114"	127"	5,200 lbs.	Dual, 16"	105-150"	35-50 GPM at 4000 psi

Specifications:

- **Loader Needs:** High flow auxillary with 35, 40, or 50+ gpm at 4,000 psi & **hydrostatic transmission** with speed control
- **Side Discharge:** Efficiently throws snow to the right or left without using the spout
- **Telescoping Truck Loading Spout:** Reach the highest of trucks seamlessly
- **Enclosed Auger Chain:** #80 Heavy Duty chain & spring tensioned idler sprocket
- **Heavy Duty Double Auger:** Includes 16" flighting & rugged 1 1/2" grease-able bearings



	Cut Width	Cut Height	Overall Height	Weight	Auger	Chute Discharge Height	Truck Loading Discharge Height	Hydraulic Requirements
HDS 7100	84.5"	36.5"	73.7"	1,480 lbs.	Single 20"	68"	96"-141"	25-40 GPM at 2,800-4,000 psi
HDS 7101	96.7"	36.5"	73.7"	1,557 lbs.	Single, 20"	68"	96"-141"	25-40 GPM at 2,800-4,000 psi

Specifications:

- **Loader Needs:** High flow auxillary with 25-40 gpm at 2,800-4,000 psi & **hydrostatic transmission** with speed control
- **Versatile Mounting:** Attach to a variety of skid steers
- **Performance Packages:** Select the ideal valve package & control option for high performance operation season after season
- **NEW Telescoping Truck Loading Spout Option:** Load trucks with ease and increase the versatility of your blower

For more information, contact your local dealer or Sales@HitchDoc.com